

1. Installing the Driver

Caution: DO NOT connect the adapter to your computer before installing the provided driver.

Insert the provided driver CD into your CD-ROM drive. The setup program will run automatically. If not, locate and double-click the **Setup.exe** file under the Driver folder on the CD. Then follow the on-screen prompts to complete the installation.

For Windows Vista users:

- If you encounter a **User Account Control** Dialog box when attempting to install a program, enter an administrator password or click Allow to start the installation.
- When prompted to restart your computer, click Yes. Note that a reboot is always needed for a successful installation. If the reboot prompt doesn't appear, always make sure to manually reboot your computer.
- Whenever driver signature dialog box appears, always click **Install this driver software anyway**.

For Windows XP Users:

Whenever driver signature dialog box appears, always click the **Continue Anyway** to continue with the installation.

1

For Windows 2000 users:

- If prompted for system patch after running the setup file, please download and install the required patch first. After that, execute the setup file again to install the driver.
- Whenever driver compatibility dialog box appears, always click **Yes** to continue with the installation.

2. Making the Connection

Connect the smaller end of the USB cable to the adapter. Then connect the other end of the USB cable to a USB 2.0 port on your computer.

If your monitor is not yet connected to the adapter, make the connection and power on your monitor.

After the connection, Windows Vista/2000 will automatically complete the installation and an identical screen will appear on the add-on monitor. On Windows Vista, if the add-on monitor is blank, reboot your system again.

On Windows XP, a **Found New hardware Wizard** will appear. Please take these steps to complete the installation.

- Select **No**, not this time to ignore Windows Updates and click Next.
- Select **Install the software automatically** (Recommended) and click Next.
- Click **Finish** to complete the installation.
- When installation is complete, an identical screen will appear on the add-on monitor.

2

Addendum: Downloading Current Drivers

In some cases the supplied CD-ROM may become outdated or new features may become available in later revisions. The latest software may be downloaded from Gefen's website.

NOTE: You may download the software using any type of internet-capable computer, however you must run the installer file on the computer that will be using the USB to DVI adapter.

To begin, type this web address into the URL navigation bar in your internet browser, then hit the ENTER key:

<http://www.gefen.com/kvm/support/download.jsp>

You will now see a list of available software on the left hand side of the page along with the size of each software download and a gear icon next to the description (see example below).

Files	Size	Download
USB to DVI/USB to VGA Drivers (Windows 2000, Windows XP, Windows Vista, Windows 7 32 & 64 bit versions with Aero Support)	11.6 MB	
USB to DVI/USB to VGA Drivers Mac OS X (Tiger, Leopard & Snow Leopard)	2.32 MB	

Find the entry entitled "USB to DVI" and the name of your operating system (Mac or PC). Click on the gear symbol to begin the download. If asked, choose "Save" and click "OK". The download will now begin. When the download is complete, move the downloaded file to the desktop of the computer that will be using the DVI-to-USB Adapter. Unzip or unpack the file then go to the sub-folder containing the driver (if necessary) and double-click on the SETUP file. The installer will now load the software into your computer. For further instructions, please refer to the installation procedures in this manual.



Note: Before the installation is complete, it's normal that the screen flicks black a couple times.

3. Changing the Display Mode

There are several ways you can utilize the monitor attached on the adapter. The add-on monitor can be configured to use either "mirror mode" or "extended mode" (extend your Windows desktop to the add-on monitor).

To change the mode, bring out the setting dialog box by positioning the mouse anywhere on your computer desktop, right-click and select **Personalize > Display Settings** on Vista or **Properties > Settings** on XP/2000

To use mirror mode:

- In the Display drop-down menu, select the option that ends with DisplayLink Graphics Adapter.
- Uncheck the **Extend the desktop onto this monitor** box on Vista or **Extend my Windows desktop onto this monitor** box on XP/2000.



To use extended mode:

- In the **Display** drop-down menu, select the option that ends with **DisplayLink Graphics Adapter**.

3

Rev X5



QUICK INSTALLATION GUIDE

USB to DVI ADAPTER

Turns USB Into An Additional DVI Port

4

Rev X5

- Check the **Extend the desktop onto this monitor** on Vista or **Extend my Windows desktop onto this monitor** on XP/2000.

Drag the icons in the window at the top of the screen to match the physical arrangement of your primary monitor and add-on monitor.
(The add-on monitor connected to the adapter may be identified as either "2" or "3", depending on your computer, although there may not be a total of 3 screens connected.)



Caution: if you're under Windows Vista Display Driver Model (WDDM) mode, only mirror mode is supported. Also your Aero experience (the flip 3D effect) will be disabled unless you unplug the adapter from your computer. Please refer to the manual on the CD for more details.

This Quick Installation Guide describes only the basic instructions on installation. For more information, please refer to the User's Manual on the provided CD-ROM